

A dramatic, monochromatic blue-toned image of a stormy ocean. A bright lightning bolt strikes the water, creating a large splash and illuminating the scene. The sky is dark and filled with heavy clouds.


Prepare for **Impact**



**STORMFORCE**  
BY WINCORE™



# Impact by design



## 8800 Key Features



- Heavy Duty 3 1/4" Frame**
- Strategically Reinforced Vinyl Extrusions**
- Strong Thick-walled Vinyl Profiles**
- Precision-mitered, Fusion-welded Frames and Sash**
- Sealed, Multi-hollow Chambers**
- Dual-pane 1" Impact-resistant Laminated Glass**
- Standard, Energy-efficient Low E / Argon**
- Architecturally-beveled Vinyl Profiles**
- Corrosion-resistant Components**
- High-performance Glazing Compound**
- 14 Color Combinations**

### Impact-resistant Laminated Glass

When it comes to impact-resistant windows for coastal areas, the frame system, laminated glass and sealant must work together to resist the catastrophic forces applied during severe weather. Stormforce 8800 windows from Wincore® do just that. Similar to the glass used in car windshields and aircraft windows, 8800's insulating glass features an impact-resistant plastic interlayer that is bonded between two pieces of glass under heat and pressure. The interlayer remains adhered to the glass fragments and resists penetration, even if the glass pane is broken – protecting against flying debris and hurricane-force winds. In addition, laminated glass guards against forced entry – resisting repeated impacts from hammers, bricks or similar weapons. It also helps to control unwanted outside noise from entering the home and filters out 99% of the sun's most damaging rays that fade carpets and draperies.

### Warm-edge Technology

The performance of the spacer in the insulating glass is critical to the efficiency of your window as well as its longevity. The innovative U-channel spacer design creates a powerful thermal barrier that reduces the amount of heat loss conducted through the window and more effectively retains the insulating argon gas that is critical to the window's thermal performance. Because this spacer system helps keep the window glass and its edges warmer, it in turn helps to lower energy bills and keep your home more comfortable.



### Importance of Laminated Glass

During a storm, if a building is breached through a broken window, wind may enter the structure and cause an increase in air pressure. This vacuum effect could lift the roof and collapse the walls. Laminated glass helps to preserve the building envelope, keeping the wind and other elements outside.

### Available Styles



Double Slider



3-Lite End Vent  
1/4-1/2-1/4



3-Lite End Vent  
1/3-1/3-1/3



Double Hung



Casement



Awning



Picture Window



Geometric



# Double Hung 8800 Key Features



Sash profiles are reinforced with aluminum that fits tightly into pocketed vinyl chambers on all sides to provide ultimate impact-resistance performance.



Frame and sash are high-heat fusion welded at precision mitered corners for improved strength and water-tightness.



The impact-resistant 1" laminated insulating glass not only offers dependable impact performance, but also provides UV protection and improved thermal performance as well.



Continuous, integral lift rails provide fingertip ease of operation and are molded into the sash itself to prevent them from becoming loose or breaking away from sash with regular use.



A weatherstripped meeting rail, with a dual seal from the sash to the frame, creates a positive seal keeping out harsh elements.



A heavy-duty, constant force corrosion-resistant balance system provides durability and easy, smooth operation. *See next page.*



Through an innovative tilt latch designed for coastal areas, both top and bottom sash tilt in to allow for easy cleaning inside the home. *See next page.*



Covered weep holes in the sill control water drainage. *Not shown.*

## Double Hung Styles



Double Hung



2 Mullioned Double Hungs



3 Mullioned Double Hungs



Mullioned Double Hung/Picture Window/Double Hung



Double Hung Mullioned w/Transom


Structural mull available. Mullions ship separate from window units and must be assembled on project site.





### Defender Tilt Latch

Central to the design of the 8800 Double Hung is a unique, high performance tilt latch. In the locked position, the rugged latch integrates deep within the wall studs and window sash reinforcement.



### High Sill Dam

The sill dam height is 2-11/16" to further reduce water penetration.



### Corrosion-resistant Locks

Marine-grade, corrosion-resistant cam locks always remain warm to the touch and are color-matched to the window. Two locks are standard.



### Balance System

Operable sash move easily on tightly-wound coil springs that will never need adjustment.

## 8800 Double Hung Structural Performance

MAXIMUM TEST SIZE	AIR INFILTRATION RESISTANCE	WATER TEST PRESSURE	DESIGN PRESSURE	OVERALL PERFORMANCE RATING
54" x 84"	0.07 cfm/ft <sup>2</sup>	7.50 psf	+50 / -50 psf	LC-PG50
48" x 72"	0.08 cfm/ft <sup>2</sup>	9.75 psf	+60 / -65 psf	LC-PG60
54" x 76"	0.06 cfm/ft <sup>2</sup>	9.75 psf	+55 / -60 psf	LC-PG55
54" x 76"	0.05 cfm/ft <sup>2</sup>	9.75 psf	+65 / -70 psf	LC-PG65

*For testing specifications and notations, see page 13.*

**8400 Non-impact High Performance products also available.**  
**Ask your Wincore® representative for details.**

# Double Slider / 3Lite End Vent

## 8800 Key Features



Sash profiles are reinforced with aluminum to provide ultimate impact-resistance.



Frame and sash are high-heat fusion welded at precision mitered corners for strength and water-tightness.



The impact-resistant 1" laminated insulating glass not only offers dependable impact performance, but also provides UV protection and improved thermal performance.



Unique water drainage system greatly improves water evacuation and minimizes air infiltration. *Not shown.*



Dual seal sash-to-frame weatherstripping creates a premier barrier against the elements.



Marine-grade, corrosion-resistant cam locks remain warm to the touch and the colors complement all 14 available window color combinations.



Slider windows feature an innovative raised monorail track system in the sill that not only provides reinforcement, but also allows sash to glide smoothly above the dirt and debris that tends to accumulate.

### Slider Styles



Double Slider




3-Lite End Vent  
1/4-1/2-1/4



3-Lite End Vent  
1/3-1/3-1/3

Structural mull available. Mullions ship separate from window units and must be assembled on project site.






### Anti-lift Block


Not only does the Anti-lift Security Block virtually eliminate unwanted sash removal, it assists with the retention of the sash when they need to be held into the frame at the most critical of times. Illustration above left shows the anti-lift block when the sash is at rest under normal conditions, while the illustration above right shows the anti-lift block engaged with the sash under pressure during high winds.

7



### Monorail Track System


The sash of 8800 horizontal sliding windows travel securely on an aluminum monorail system. Tandem nylon rollers with stainless steel bearings resist corrosion.



## 8800 Double Slider & 3 Lite End Vent Structural Performance

MAXIMUM TEST SIZE	AIR INFILTRATION RESISTANCE	WATER TEST PRESSURE	DESIGN PRESSURE	OVERALL PERFORMANCE RATING
DS 74" x 62"	0.01 cfm/ft2	9.75 psf	+55 / -55 psf	LC-PG55
DS 74" x 63"	0.02 cfm/ft2	9.75 psf	+50 / -55 psf	LC-PG50
DS 74" x 63"	0.02 cfm/ft2	9.75 psf	+65 / -75 psf	LC-PG65
EV (333) 110" x 62"	0.01 cfm/ft2	9.75 psf	+55 / -55 psf	LC-PG55
EV (333) 86.5" x 62"	0.02 cfm/ft2	9.75 psf	+50 / -55 psf	LC-PG50
EV (333) 86.5" x 62"	0.02 cfm/ft2	9.75 psf	+60 / -65 psf	LC-PG60
EV (424) 110" x 62"	0.04 cfm/ft2	9.75 psf	+45 / -45 psf	LC-PG45
EV (424) 112" x 63"	0.02 cfm/ft2	9.75 psf	+50 / -55 psf	LC-PG50
EV (424) 112" x 63"	0.01 cfm/ft2	9.75 psf	+60 / -65 psf	LC-PG60

*For testing specifications and notations, see page 13.*



### Multi-hollow Profiles

Vinyl profiles are chambered to ensure rigidity, strengthen the overall unit and improve the energy efficiency of the window.

**8400 Non-impact High Performance products also available.**  
**Ask your Wincore® representative for details.**

# Casement & Awning

## 8800 Key Features



Fully concealed multi-point lock system with a zippered locking effect ensures engagement of top lock point. Nesting folding handle is designed to minimize interference with window treatments such as curtains and blinds.



The sturdy frames and sash are made from thick premium quality vinyl extrusions and do not require additional reinforcement.



Operators utilize a sealable housing to reduce air and water infiltration. *Not shown.*



Heavy-gage steel hinges allow exterior glass pane to be cleaned from inside the home, and open the window to almost 90 degrees for maximum ventilation. A stainless steel hardware option offers an extended warranty. *Not shown.*



Triple weatherstripping creates remarkable air-tightness to prevent drafts and help reduce heating and air conditioning costs.



The impact-resistant 1" laminated insulating glass not only offers dependable impact performance, but also provides UV protection and improved thermal performance.

### 8800 Casement & Awning Structural Performance

MAXIMUM TEST SIZE	AIR INFILTRATION RESISTANCE	WATER TEST PRESSURE	DESIGN PRESSURE	OVERALL PERFORMANCE RATING
CS 36" x 72"	<0.01 cfm/ft2	7.50 psf	+50 / -50 psf	LC-PG50
CS 36" x 72"	<0.01 cfm/ft2	15.00 psf	+55 / -55 psf	LC-PG55
CS 36" x 72"	<0.01 cfm/ft2	15.00 psf	+65 / -70 psf	LC-PG65
AW 53" x 32"	<0.01 cfm/ft2	9.75 psf	+50 / -50 psf	LC-PG50
AW 53" x 32"	<0.01 cfm/ft2	15.00 psf	+55 / -55 psf	LC-PG55

*For testing specifications and notations, see page 13.*

### Casement and Awning Styles






Structural mull available. Mullions ship separate from window units and must be assembled on project site.

# Picture Window

## 8800 Key Features



-  Architecturally-beveled exterior frame complements the frames of other 8800 operating units.
-  The impact-resistant 1" laminated insulating glass not only offers dependable impact performance, but also provides UV protection and improved thermal performance.
-  Vinyl extrusions are impact and corrosion-resistant and their multi-hollow chambered interior design adds strength and helps improve thermal performance.



### 8800 Picture Window Structural Performance

MAXIMUM TEST SIZE	AIR INFILTRATION RESISTANCE	WATER TEST PRESSURE	DESIGN PRESSURE	OVERALL PERFORMANCE RATING
48" x 60"	<0.01 cfm/ft2	7.50 psf	+50 / -50 psf	LC-PG50
37" x 84"	0.04 cfm/ft2	7.50 psf	+50 / -50 psf	LC-PG50
64" x 64"	<0.01 cfm/ft2	7.50 psf	+50 / -50 psf	LC-PG50
72" x 72"	<0.01 cfm/ft2	12.00 psf	+50 / -50 psf	LC-PG50
64" x 64"	<0.01 cfm/ft2	12.00 psf	+65 / -65 psf	LC-PG65
37" x 84"	<0.01 cfm/ft2	9.75 psf	+65 / -65 psf	LC-PG65
72" x 72"	<0.01 cfm/ft2	9.75 psf	+65 / -65 psf	LC-PG65
76" x 63"	<0.01 cfm/ft2	15.00 psf	+65 / -70 psf	LC-PG65

*For testing specifications and notations, see page 13.*

#### Fixed Unit Styles



Picture Window



Geometric Windows  
*Limited Styles*

**8400 Non-impact High Performance products also available.**  
Ask your Wincore® representative for details.

# Sliding Patio Doors

## 8800 Key Features



1

Fully concealed aluminum interlock system with a zippered locking effect ensures engagement of top lock point. This integral system adds paramount strength and security without restricting the outside view.

2

The sturdy frames and sash are made from thick premium quality vinyl extrusions and are chambered for maximum rigidity.

3

Sash panels feature full-length steel reinforcement – providing increased impact resistance where it is needed most.

4

A high water barrier bar at the sill helps prevent water penetration at the sill track system. *Not shown.*

5

Extruded screen frames feature a patented, adjustable, spring-loaded suspension system at the corners and is designed not to derail or jam. *Not shown.*

6

The impact-resistant 1" laminated insulating glass not only offers dependable impact performance, but also provides UV protection and improved thermal performance. *Not shown.*



Standard Low E / Argon with U-channel spacer design ensure 8800 Sliding Patio Doors meet ENERGY STAR® guidelines.



**Draft Protection**

Triple weatherstripping at rails and double weatherstripping at junction, improve insulation and creates incredible air-tightness to prevent drafts and help reduce heating and air conditioning costs.



**Exterior Keyed Lock**

Standard exterior keyed lock and available with optional interior footbolt.

**8800 Sliding Patio Door Structural Performance**

MAXIMUM TEST SIZE	AIR INFILTRATION RESISTANCE	WATER TEST PRESSURE	DESIGN PRESSURE	OVERALL PERFORMANCE RATING
94.5" x 94.5"	0.07 cfm/ft2	7.50 psf	+50 / -50 psf	LC-PG50
96" x 96"	0.02 cfm/ft2	9.75 psf	+50 / -55 psf	LC-PG50
138.9" x 94.5"	0.07 cfm/ft2	7.50 psf	+50 / -50 psf	LC-PG50

*For testing specifications and notations, see page 13.*

**Smooth Glide Track System**

Operating panels slide effortlessly, regardless of door size, because of an exclusive, patented sliding system that features adjustable dual, tandem 1" wheels to ensure smooth, easy and quiet operation.



# 8800 High Performance / Impact / Non-HVHZ

Structural Performance		MAXIMUM TEST SIZE	AIR INFILTRATION RESISTANCE	WATER TEST PRESSURE	DESIGN PRESSURE	OVERALL PERFORMANCE RATING	FBC APPROVAL
★	Double Hung (DS / .090 PVB)	48" x 72"	0.08 cfm/ft2	9.75 psf	+60 / -65 psf	LC-PG60	FL15819
★	Double Hung (DS / .090 PVB)	54" x 84"	0.07 cfm/ft2	7.50 psf	+50 / -50 psf	LC-PG50	FL15819
★	Double Hung (DST / .090 PVB)	54" x 76"	0.06 cfm/ft2	9.75 psf	+55 / -60 psf	LC-PG55	FL15819
★	Double Hung (DST / .090 SGP)	54" x 76"	0.05 cfm/ft2	9.75 psf	+65 / -70 psf	LC-PG65	FL15819
★	Horizontal Slider (XX) (DS / .090 PVB)	74" x 62"	0.01 cfm/ft2	9.75 psf	+55 / -55 psf	LC-PG55	FL16092
★	Horizontal Slider (XX) (DST / .090 PVB)	74" x 63"	0.02 cfm/ft2	9.75 psf	+50 / -55 psf	LC-PG50	FL16092
★	Horizontal Slider (XX) (DS T / .090 SGP)	74" x 63"	0.02 cfm/ft2	9.75 psf	+65 / -75 psf	LC-PG65	FL16092
★	Horizontal Slider (XOX - 333) (DS / .090 PVB)	110" x 62"	0.01 cfm/ft2	9.75 psf	+55 / -55 psf	LC-PG55	FL16092
★	Horizontal Slider (XOX - 424) (DS / .090 PVB)	110" x 62"	0.04 cfm/ft2	9.75 psf	+45 / -45 psf	LC-PG45	FL16092
★	Horizontal Slider (XOX - 424) (DST / .090 PVB)	112" x 63"	0.02 cfm/ft2	9.75 psf	+50 / -55 psf	LC-PG50	FL16092
★	Horizontal Slider (XOX - 424) (DST / .090 SGP)	112" x 63"	0.01 cfm/ft2	9.75 psf	+60 / -65 psf	LC-PG60	FL16092
	Picture (Fixed) Window (DS / .090 PVB)	48" x 60"	<0.01 cfm/ft2	7.50 psf	+50 / -50 psf	LC-PG50	FL15816
	Picture (Fixed) Window (DS / .090 PVB)	37" x 84"	0.04 cfm/ft2	7.50 psf	+50 / -50 psf	LC-PG50	FL15816
	Picture (Fixed) Window (3S Glass / .090 PVB)	64" x 64"	<0.01 cfm/ft2	7.50 psf	+50 / -50 psf	LC-PG50	FL15816
	Picture (Fixed) Window (3S Glass / .090 SGP)	72" x 72"	<0.01 cfm/ft2	12.00 psf	+50 / -50 psf	LC-PG50	FL15816
	Picture (Fixed) Window (DST / .090 SGP)	64" x 64"	<0.01 cfm/ft2	12.00 psf	+65 / -65 psf	LC-PG65	FL15816
	Picture (Fixed) Window (DST / .090 SGP)	37" x 84"	<0.01 cfm/ft2	9.75 psf	+65 / -65 psf	LC-PG65	FL15816
	Picture (Fixed) Window (3ST Glass / .090 SGP)	72" x 72"	<0.01 cfm/ft2	9.75 psf	+65 / -65 psf	LC-PG65	FL15816
	Picture/Geometric (Fixed) Window (3ST Glass / .090 SGP)	76" x 63"	<0.01 cfm/ft2	15.00 psf	+65 / -70 psf	LC-PG65	FL15816
	Casement (DS / .090 PVB)	36" x 72"	<0.01 cfm/ft2	7.50 psf	+50 / -50 psf	LC-PG50	FL15817
	Casement (DST / .090 PVB)	36" x 72"	<0.01 cfm/ft2	15.00 psf	+55 / -50 psf	LC-PG55	FL15817
	Casement (DS T / .090 SGP)	36" x 72"	<0.01 cfm/ft2	15.00 psf	+65 / -70 psf	LC-PG65	FL15817
	Awning (DS / .090 PVB)	53" x 32"	<0.01 cfm/ft2	9.75 psf	+50 / -50 psf	LC-PG50	FL15818
	Awning (DST / .090 PVB)	53" x 32"	<0.01 cfm/ft2	15.00 psf	+55 / -55 psf	LC-PG55	FL15818
	Sliding Patio Door (DST / .090 PVB)	94.5" x 94.5"	0.07 cfm/ft2	7.50 psf	+50 / -50 psf	LC-PG50	FL16216
	Sliding Patio Door (DST / .090SGP)	96" x 96"	0.02 cfm/ft2	9.75 psf	+50 / -55 psf	LC-PG50	FL16216
	Sliding Patio Door (DST / .090 PVB)	138.9" x 94.5"	0.07 cfm/ft2	7.50 psf	+50 / -50 psf	LC-PG50	FL16216
Thermal Performance	LOW E (Surface 2) / CLEAR			LOW E (Surface 2) / LOW E (Surface 4)			
	U-Factor	SHGC	VT	U-Factor	SHGC	VT	
	Double Hung (DS / .090 PVB)	0.32	0.23	0.44	0.28	0.21	0.40
	Double Hung (DS / .090 SGP)	0.32	0.23	0.44	0.28	0.21	0.39
	Horizontal Slider (XX) (DS / .090 PVB)	0.32	0.22	0.44	0.28	0.21	0.40
	Horizontal Slider (XX) (DS / .090 SGP)	0.32	0.22	0.43	0.28	0.21	0.39
	Horizontal Slider (XOX - 333) (DS / .090 PVB)	0.32	0.22	0.44	0.28	0.21	0.40
	Horizontal Slider (XOX - 424) (DS / .090 PVB)	0.32	0.22	0.44	0.28	0.21	0.40
	Horizontal Slider (XOX - 424) (DS / .090 SGP)	0.32	0.22	0.43	0.28	0.21	0.39
	Picture (Fixed) Window (DS / .090 PVB)	0.26	0.25	0.50	0.22	0.23	0.45
	Picture (Fixed) Window (3S Glass / .090 PVB)	0.26	0.25	0.50	0.22	0.24	0.46
	Picture (Fixed) Window (DS / .090 SGP)	0.26	0.25	0.49	0.22	0.23	0.45
	Picture/Geometric (Fixed) Window (3S Glass / .090 SGP)	0.26	0.25	0.49	0.22	0.23	0.45
	Casement (DS / .090 PVB)	0.26	0.20	0.40	0.23	0.19	0.36
	Casement (DS / .090 SGP)	0.26	0.20	0.29	0.23	0.19	0.36
	Awning (DS / .090 PVB)	0.27	0.20	0.39	0.24	0.19	0.36
	Sliding Patio Door (DST / .090 PVB) and (DST / .090 SGP)	0.31	0.23	0.44	0.27	0.21	0.40

## NOTES

- All structural testing performed on non-HVHZ approved products was done so in accordance with AAMA/WDMA/CSA 101/LS.2/A440
- All impact testing performed on non-HVHZ was done so in accordance with ASTM E 1886 & ASTM E 1996 ( Missile "D" Windzone 4)
- All Insulated Glass Units (IGUs) are certified in accordance with ASTM E 2190, per NFRC requirement
- U-Factor was determined by NFRC 100-2010
- SHGC (Solar Heat Gain Coefficient) was determined by NFRC 200-2010
- VT (Visible Transmittance) was determined by NFRC 200-2010
- The use of Capillary Tubes will eliminate the use of Argon gas in the insulated glass unit and will therefore have detrimental impact to the thermal performance of the IGU
- All thermal performance values listed reflect the use of NO GRIDS
- Additional simulations are available upon request

★ **Double Low E required on these Window Styles to Qualify for Energy Star® Version 5 in the Northern Regions.**

DS = Double Strength Glass  
 DST = Tempered Double Strength Glass  
 3S = Annealed Triple Strength Glass  
 3ST = Tempered 3/16" Glass

# 8800 High Performance / Impact / HVHZ Certified

Structural Performance	MAXIMUM TEST SIZE	AIR INFILTRATION RESISTANCE	WATER TEST PRESSURE	DESIGN PRESSURE	OVERALL PERFORMANCE RATING	FBC APPROVAL
★ Double Hung (DST / .090 PVB)	54" x 76"	0.06 cfm/ft2	9.75 psf	+55 / -60 psf	LC-PG55	FL15819
★ Double Hung (DST / .090 SGP)	54" x 76"	0.05 cfm/ft2	9.75 psf	+65 / -70 psf	LC-PG65	FL15819
★ Horizontal Slider (XX) (DST / .090 PVB)	74" x 63"	0.02 cfm/ft2	9.75 psf	+50 / -55 psf	LC-PG50	FL16092
★ Horizontal Slider (XX) (DS T / .090 SGP)	74" x 63"	0.02 cfm/ft2	9.75 psf	+65 / -75 psf	LC-PG65	FL16092
★ Horizontal Slider (XOX - 424) (DST / .090 PVB)	112" x 63"	0.02 cfm/ft2	9.75 psf	+50 / -55 psf	LC-PG50	FL16092
★ Horizontal Slider (XOX - 424) (DST / .090 SGP)	112" x 63"	0.01 cfm/ft2	9.75 psf	+60 / -65 psf	LC-PG60	FL16092
Picture (Fixed) Window (3ST Glass / .090 SGP)	76" x 63"	<0.01 cfm/ft2	15.00 psf	+65 / -70 psf	LC-PG65	FL15816
Geometric (Fixed) Window (3ST Glass / .090 SGP)	76" x 63"	<0.01 cfm/ft2	15.00 psf	+65 / -70 psf	LC-PG65	FL15816
Casement (DST / .090 PVB)	36" x 72"	<0.01 cfm/ft2	15.00 psf	+55 / -50 psf	LC-PG55	FL15817
Casement (DS T / .090 SGP)	36" x 72"	<0.01 cfm/ft2	15.00 psf	+65 / -70 psf	LC-PG65	FL15817
Awning (DST / .090 PVB)	53" x 32"	<0.01 cfm/ft2	15.00 psf	+55 / -55 psf	LC-PG55	FL15818
Sliding Patio Door (DST / .090SGP)	96" x 96"	0.02 cfm/ft2	9.75 psf	+50 / -55 psf	LC-PG50	FL16216

Thermal Performance	LOW E (Surface 2) / CLEAR			LOW E (Surface 2) / LOW E (Surface 4)		
	U-Factor	SHGC	VT	U-Factor	SHGC	VT
Double Hung (DS / .090 PVB)	0.32	0.23	0.44	0.28	0.21	0.40
Double Hung (DS / .090 SGP)	0.32	0.23	0.44	0.28	0.21	0.39
Horizontal Slider (XX) (DS / .090 PVB)	0.32	0.22	0.44	0.28	0.21	0.40
Horizontal Slider (XX) (DS / .090 SGP)	0.32	0.22	0.43	0.28	0.21	0.39
Horizontal Slider (XOX - 333) (DS / .090 PVB)	0.32	0.22	0.44	0.28	0.21	0.40
Horizontal Slider (XOX - 424) (DS / .090 PVB)	0.32	0.22	0.44	0.28	0.21	0.40
Horizontal Slider (XOX - 424) (DS / .090 SGP)	0.32	0.22	0.43	0.28	0.21	0.39
Picture (Fixed) Window (3S Glass / .090 SGP)	0.26	0.25	0.49	0.22	0.23	0.45
Geometric (Fixed) Window (3S Glass / .090 SGP)	0.26	0.25	0.49	0.22	0.23	0.45
Casement (DS / .090 PVB)	0.26	0.20	0.40	0.23	0.19	0.36
Casement (DS / .090 SGP)	0.26	0.20	0.29	0.23	0.19	0.36
Awning (DS / .090 PVB)	0.27	0.20	0.39	0.24	0.19	0.36
Sliding Patio Door (DST / .090 PVB) and (DST / .090 SGP)	0.31	0.23	0.44	0.27	0.21	0.40

**NOTES**


- All structural testing performed on non-HVHZ approved products was done so in accordance with AAMA/WDMA/CSA 101/I.S.2/A440
- All impact testing performed on non-HVHZ was done so in accordance with ASTM E 1886 & ASTM E 1996 ( Missile "D" Windzone 4)
- All structural testing performed on HVHZ approved products was done so in accordance with TAS 202
- All impact testing performed on HVHZ approved products was done so in accordance with TAS 201 and TAS 203
- All Insulated Glass Units (IGUs) are certified in accordance with ASTM E 2190, per NFRC requirement
- U-Factor was determined by NFRC 100-2010
- SHGC (Solar Heat Gain Coefficient) was determined by NFRC 200-2010
- VT (Visible Transmittance) was determined by NFRC 200-2010
- The use of Capillary Tubes will eliminate the use of Argon gas in the insulated glass unit and will therefore have detrimental impact to the thermal performance of the IGU
- All thermal performance values listed reflect the use of NO GRIDS
- Additional simulations are available upon request

★ Double Low E Required on these Window Styles to Qualify for Energy Star® Version 5 in the Northern Regions.

DS = Double Strength Glass  
 DST = Tempered Double Strength Glass  
 3S = Annealed Triple Strength Glass  
 3ST = Tempered 3/16" Glass




# 8800 High Performance / Impact – Cross Sections




Vertical

## Double Hung




Horizontal

## Double Slider




Horizontal




Vertical

## 3-Lite End Vent Slider




Horizontal



Vertical


# 8800 High Performance / Impact – Cross Sections

Picture Window




Horizontal / Vertical

Casement / Awning




Horizontal / Vertical


Sliding Patio Door



Horizontal



**NEED CROSS SECT. DRAWING**



Vertical



# 8400 High Performance / Non-Impact

Structural Performance		MAXIMUM TEST SIZE	AIR INFILTRATION RESISTANCE	WATER TEST PRESSURE	DESIGN PRESSURE	OVERALL PERFORMANCE RATING	FBC APPROVAL			
*	Double Hung (DS)	48" x 72"	<0.01 cfm/ft2	9.75 psf	+60 / -65 psf	LC-PG60	FL15819			
*	Double Hung (DS)	54" x 84"	0.02 cfm/ft2	7.50 psf	+50 / -50 psf	LC-PG50	FL15819			
*	Double Hung (DST)	54" x 76"	0.10 cfm/ft2	9.75 psf	+65 / -70 psf	LC-PG65	FL15819			
*	Horizontal Slider (XX) (DS)	74" x 62"	<0.01 cfm/ft2	9.75 psf	+50 / -50 psf	LC-PG50	FL16092			
*	Horizontal Slider (XX) (DST)	74" x 63"	0.07 cfm/ft2	9.75 psf	+60 / -65 psf	LC-PG60	FL16092			
*	Horizontal Slider (XOX - 333) (DS)	110" x 62"	0.02 cfm/ft2	9.75 psf	+50 / -50 psf	LC-PG50	FL16092			
*	Horizontal Slider (XOX - 424) (DS)	110" x 62"	0.01 cfm/ft2	9.75 psf	+50 / -50 psf	LC-PG50	FL16092			
*	Horizontal Slider (XOX - 424) (DST)	112" x 63"	0.07 cfm/ft2	9.75 psf	+60 / -65 psf	LC-PG60	FL16092			
	Picture (Fixed) Window (DS)	48" x 60"	<0.01 cfm/ft2	12.00 psf	+50 / -50 psf	LC-PG50	FL15816			
	Picture (Fixed) Window (3ST Glass)	64" x 64"	<0.01 cfm/ft2	12.00 psf	+65 / -65 psf	LC-PG65	FL15816			
	Picture (Fixed) Window (3ST Glass)	72" x 72"	<0.01 cfm/ft2	7.50 psf	+50 / -50 psf	LC-PG50	FL15816			
	Picture (Fixed) Window (DST)	37" x 84"	<0.01 cfm/ft2	9.75 psf	+65 / -65 psf	LC-PG65	FL15816			
	Picture (Fixed) Window (DST)	72" x 72"	<0.01 cfm/ft2	9.75 psf	+55 / -65 psf	LC-PG55	FL15816			
	Picture (Fixed) Window (3ST Glass)	76" x 63"	<0.01 cfm/ft2	15.00 psf	+80 / -80 psf	LC-PG80	FL15816			
	Casement (DS)	36" x 71.85"	<0.01 cfm/ft2	7.50 psf	+50 / -50 psf	LC-PG50	FL15817			
	Casement (DST)	36" x 72"	0.02 cfm/ft2	15.00 psf	+65 / -65 psf	LC-PG65	FL15817			
	Awning (DS)	53" x 32"	<0.01 cfm/ft2	9.75 psf	+55 / -55 psf	LC-PG55	FL15818			
	Awning (DST)	53" x 32"	<0.01 cfm/ft2	15.00 psf	+65 / -65 psf	LC-PG65	FL15818			
Thermal Performance		LOW E (Surface 2) / CLEAR			LOW E (Surface 2) / LOW E (Surface 4)			LOW E (Surface 2) / CLEAR / Low E (Surface 5)		
		U-Factor	SHGC	VT	U-Factor	SHGC	VT	U-Factor	SHGC	VT
	Double Hung (DS)	0.33	0.23	0.45	0.29	0.21	0.41	0.27	0.19	0.32
	Horizontal Slider (XX) (DS)	0.33	0.22	0.45	0.29	0.21	0.40	0.26	0.19	0.31
	Horizontal Slider (XOX - 333) (DS)	0.33	0.22	0.45	0.29	0.21	0.40	0.26	0.19	0.31
	Horizontal Slider (XOX - 424) (DS)	0.33	0.22	0.45	0.29	0.21	0.40	0.26	0.19	0.31
	Fixed Window (3S Glass)	0.27	0.25	0.50	0.23	0.24	0.46	N/A	N/A	N/A
	Fixed Window (DS)	0.28	0.25	0.51	0.23	0.24	0.46	0.21	0.22	0.36
	Casement (DS)	0.28	0.21	0.41	0.24	0.19	0.37	0.21	0.17	0.29
	Awning (DS)	0.28	0.21	0.41	0.24	0.19	0.37	0.21	0.18	0.29

## NOTES

- All structural testing performed was done so in accordance with AAMA/WDMA/CSA 101/1.S.2/A440
- All Insulated Glass Units (IGUs) are certified in accordance with ASTM E 2190, per NFRC requirement
- U-Factor was determined by NFRC 100-2010
- SHGC (Solar Heat Gain Coefficient) was determined by NFRC 200-2010
- VT (Visible Transmittance) was determined by NFRC 200-2010
- The use of Capillary Tubes will eliminate the use of Argon gas in the insulated glass unit and will therefore have detrimental impact to the thermal performance of the IGU
- All thermal performance values listed reflect the use of NO GRIDS
- Additional simulations are available upon request


★ **Double Low E required on these Window Styles to Qualify for Energy Star® Version 5 in the Northern & North Central Regions.**

DS = Double Strength Glass  
 DST = Tempered Double Strength Glass  
 3S = Annealed Triple Strength Glass  
 3ST = Tempered 3/16" Glass




# 8400 High Performance / Non-Impact – Cross Sections

Double Hung




Vertical




Horizontal

Double Slider




Horizontal




Vertical

Casement / Awning




Horizontal / Vertical

3-Lite End Vent Slider




Vertical



Horizontal

Picture Window



Horizontal / Vertical

# DECORATIVE OPTIONS

## Grids & Grid Patterns



Colonial



Perimeter

Optional contoured grids are located inside the insulating glass unit to provide a smooth cleaning surface. Available in two distinct patterns. Choose from White, Tan or Clay grids, or White Oak, Light Oak, Dark Oak, Cherry or Maple Woodgrain grids.

## Interior/Exterior Colors



White



Tan



Clay

## Interior Woodgrains



White Oak



Dark Oak



Light Oak



Maple



Cherry



All 8800 and 8400 windows feature contoured vinyl profiles.



## The power of collective **thinking.**

In this business, everyone knows that great people working together end up providing great windows and doors. That's why when we set out to design and build the best windows and doors in the industry, we focused on people first. People with advanced technical knowledge. People who know how to do things right the first time. But most importantly, people who realize that integrity and trust are not simply words, but a way of life. With more than 200 years of combined experience under our belts, you can clearly see our promise of quality and innovation in every window and door we make. Not to mention how we go about making them. To us, it's about creating an environment that brings out the best in everyone, and accepts nothing less. It's about doing things the way they should be done, not necessarily the way they've always been done. It's about giving back to our communities and the things that matter most. And it's about family – ours, as well as yours. At Wincore®, it's not about being the biggest. It's about being the best. Because to us, that's the way it should be.



*The way it should be.™*

1-866-WINCORE [www.wincorewindows.com](http://www.wincorewindows.com)

250 Staunton Avenue, Parkersburg, WV 26104

The information is correct at the time of printing. Changes to the product(s) may have occurred since time of printing. Not all product styles and/or options are available in all areas, so please consult your sales representative prior to purchasing. Wincore® is a registered trademark and The way it should be.™ is a trademark of Wincore Window Company, LLC. Tough Enough to Wear Pink is a licensed trademark of Terry Wheatley and is used by permission. Intercept® is a registered trademark of PPG Industries, Inc. Printed in U.S.A. ©2013 Wincore Windows and Doors. All rights reserved.



Proud to support breast cancer research.  
Full details available at  
[www.wincorewindows.com](http://www.wincorewindows.com)